



*Rear Panel

IP CAMERAS **8CH** NETWORK VIDEO RECORDER

8CH 720p / 4CH 1080p • 1xHDMI • 1xVGA • 1xBNC • ONVIF Version 2.0/2.1/2.2



SECURITY IN YOUR HAND
Multi-Channel Remote Live View

FEATURES

- Up to 8 CH with 720p / 4CH 1080p Realtime Live View
- H.264/MPEG-4 Dual Codec Decoding
- Up to 2MP Resolution
- HDMI / VGA / BNC Simultaneous Video Output
- 4 Channel Synchronous Realtime Playback
- ONVIF Version 2.0/2.1/2.2 Conformance
- Support 2 SATA HDDs up to 3TB
- Multiple Network Monitoring: Web Viewer, CMS & Mobile



*Accessories

NVST SR508

SYSTEM	
Operating System	Embedded LINUX
VIDEO & AUDIO	
IP Camera Input	8 Channel
Two-way Talk	1 Channel Input, 1 Channel Output, BNC
DISPLAY	
Interface	1 HDMI, 1 VGA, 1 BNC
Resolution	800×600;1024×768;1280×1024;1440×900;1920×1080
Display Split	1/4/8
OSD	Camera Title, Time, Video Loss, Camera Lock, Motion Detection, Recording
RECORDING	
Compression	H.264 (High Profile@Level4.2) / MPEG-4
Resolution	1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480)
Record Rate	Max 4CH@1080P or 8CH@720P or 8CH@D1
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
VIDEO DETECTION & ALARM	
Trigger Events	Recording, Alarm, Video Push, Email, Buzzer
Video Detection	Motion Detection, Video Loss, HDD Loss
Alarm Input	4 Channel
Relay Output	1 Channel
PLAYBACK & BACKUP	
Sync Playback	1CH WITH1080P/4CH WITH 720P
Search Mode	Time/Date, Alarm, MD & Exact Search (Accurate to second)
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Network
NETWORK	
Ethernet	RJ-45 port (10/100M)
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, DHCP, DNS, PPPoE, DDNS
Max. User Access	20 Users
Mobile Phone	IPhone, IPad, Android
STORAGE	
Internal HDD	2 SATA Ports, up to 3TB
AUXILIARY INTERFACE	
USB Interface	3 Ports (1 Rear), USB2.0
RS232	Yes
RS485	1 Port, For PTZ Control
GENERAL	
Power Supply	DC12V/2A
Power Consumption	10W (without HDD)
Working Environment	-10 ~ +55 °C / 10~90%RH / 86~106kpa
Dimension(W×D×H)	1U, 315×285×50 (mm)