

PVT-8M Series | 8 Channel 8MP (4K/UHD) H.265 Penta-brid (TVI/AHD/CVI/IP/960H) DVR System, 1 × SATA



FEATURES

- 4K Video Output
- Programmable spot out resolution up to 4K@60
- Choose any video output as programmable spot out (HDMI / VGA/ Composite)
- Megabit Ethernet
- H.265 CODEC Recording. Up to 30% more recording time
- 8 Channel Audio Input
- Full GUI with alpha blending
- Individual setting of resolution, frame rates and picture quality
- Instant Replay
- Digital Zoom
- Mouse Control
- Weekly scheduler with holiday by 10 minutes setting

PVT-8M Series | 8 Channel 8MP (4K/UHD) H.265 Penta-brid (TVI/AHD/CVI/IP/960H) DVR System, 1 × SATA

- Covert, Disable and Private function of cameras
- Motion Detection with 576 area setting
- Relay alarm output
- PTZ control by RS-485
- Daylight Saving Time and Network Time Setting
- Multi User Authority up to 8 Users
- De-interlacer upon live and playback
- 22 languages with full graphic
- Individual Network port setting
- Auto Deletion
- Import and Export the configuration
- Interactive setup via network
- POS Interface
- No Mirroring
- Dual CODEC engine for independent video transmission

SPECIFICATIONS

Video	
Camera input	8 BNC
Individual HD/Analog selectable	Analog, AHD, TVI, CVI, IP
Available source	TVI/AHD/CVI 720p25,30/1080p25,30/3MP@18 ~ 30/4MP@12 ~ 30/5MP@20/8MP@15 Composite/960H/Mixed
IP Camera Spec	ONVIF 2.3, RTSP, H.264, H.265, dual stream use gigabit ethernet hub
IP Camera Num	8
IP Camera Resolution	~ 4K@30
IP Camera Restriction	Cannot setup Private ZONE Cannot support Timestamp
Output	1 HDMI (Main Display or Programmable HD Spot, ~UHD@60) 1 VGA (Main Display or Programmable HD Spot, ~1080p60) 1 Composite (Programmable SPOT)
Audio	
Audio input	8 RCA

PVT-8M Series | 8 Channel 8MP (4K/UHD) H.265 Penta-brid (TVI/AHD/CVI/IP/960H) DVR System, 1 × SATA

Output	1 RCA
Sensor In	8 (NC, NO selectable)
Alarm out	1 relay
Operating System	Embedded Linux OS
Display	
Speed	Real Time
Resolution (Pixel)	1280 × 1024, 1280 × 720, 1920 × 1080, 4M, UHD
Split screen	1,4,6,8,9
Main Recording	
CODEC	H.265
Resolution (Pixel)	8MP : 8MP, 1080p 5MP : 5MP, 720p 4MP : 4MP, 720p 3MP : 3MP, 720p 1080p : 1080p, 720p 720p : 720p, 960 × 540 960H, Composite : 960H, D1
Picture quality	4 steps (Super, High, Medium, Low)
Speed	120fps @ 4MP
Dual Recording	
CODEC	H.264
Resolution (Pixel)	640 × 352
Playback	
Display	1,4,6,8,9
Search mode	Calendar, Event ,POS , Panorama, Thumbnail
Speed	120fps
Fast/Slow speed	Normal, REW & FF [recorded speed × 2, × 4, × 8, × 16,x32,x64,x1/2,x1/4], Frame to frame, Pause
Network (Individual setting of resolution, frame rates and picture quality)	
Network Interface	Megabit Ethernet
High Resolution (Pixel)	same as Main Recording
Low Resolution (Pixel)	720, 1080p, 3MP, 4MP, 5MP, 8MP : 480 × 256 960H, Composite : CIF

PVT-8M Series | 8 Channel 8MP (4K/UHD) H.265 Penta-brid (TVI/AHD/CVI/IP/960H) DVR System, 1 × SATA

Speed	70fps @ 1080p
Protocol	TCP/IP, HTTP, DHCP
Application	Windows 7 / 8 / 10 (PC Client system& IE) / MAC
Web Browser	Internet Explorer, Safari, Chrome, Firefox
Smart phone App	Android, iPhone for live and search
Backup	
Interface	USB 2.0 × 2
Backup device	External HDD, CD&DVD-RW, Network, Thumb Drive
RAID	N/A
The number of HDD	1 SATA(No capacity limit ; 8TB of more)
Others	
Power Consumption	24W
Operating Temperature	5 ~ 40°C(41 ~ 104F)
Relative Humidity	Maximum 80% non-condensing
Dimension	11.81" × 8.27" × 1.89" (300 × 210 × 48mm)