T28 Weighing scales

Universal Retail Systems
Time Tested POS Solutions

Specifications

Dimensions:	243x239x158mm
Display:	25mm digit LCD display, with white LED backlight
Capacities:	3kg~25k
Pan size:	230 x 190 mm
Keyboard:	3keys (Membarne keyboard)
Housing:	ABS plastic
Max. Divisions:	3,000e; 2x3, 000e; 15,000d
ADC:	Sigma delta
ADC update	≤ 1/10 second
Operate Temp:	-10°~+ 40°C
Power:	AC adapter (12V/500mA) or rechargeable battery (6V/4Ah)
Gross weight:	3.5kg

Features

Gigh mobility: battery operation, compact, light weight construction, it is suitable for the use in severak location (kitchen, sales office, cafeteria, Food industry-Laboratory etc.)

Easy to clean: stainless steel pan. Its smooth surfaces make it simple to clean

Easy to read: 6 digits 25mm digits high LCD display, with white backlight.

Optional rear display

Full funtion: unit change, are, zero

- Waterproof housing designed, rugged and dependable
- Standard SST pan
- Battery provide up to 70 hours of continuous use (without bacjlight)
- Optional rear display
- Optional initial - verification

T-Scale

580 E3rd St C, Oxnard, CA93030, USA
support@urpos.com
(+1) 805 483 937

T28 Weighing Scales

Dimensions (mm)







Options



Standard

Model Name	Capacity	Readability	Division	Approx. weight	Approval
T28-3K	3kg	0.2g	15,000d	3.5kg	CE
T28-6K	6kg	0.5g	15,000d	3.5kg	CE
T28-15K	15kg	1g	15,000d	3.5kg	CE
T28-25K	25kg	2g	15,000d	3.5kg	CE
T28-3K-M	3kg	1g	3,000e	3.5kg	CE,OIML
T28-6K-M	6kg	2g	3,000e	3.5kg	CE,OIML
T28-15K-M	15kg	5g	3,000e	3.5kg	CE,OIML
T28-25K-M	25kg	10g	3,000e	3.5kg	CE,OIML
T28-6K-MR	6kg	1g/2g	2x3,000e	3.5kg	CE,OIML
T28-15K-MR	15kg	2g/5g	2x3,000e	3.5kg	CE,OIML
T28-25K-MR	25kg	5/10g	2x3,000e	3.5kg	CE,OIML

Universal Retail Systems
(+1) 805 483 937 support@urpos.com
580 E3rd St C, Oxnard, CA93030, USA